

# FELCO 8 Classic

Pruning shear - High performance - Ergonomic

Made in Switzerland by FELCO
















- Reliable: comfortable, light, sturdy handles made of forged aluminium with a lifetime guarantee\* / blade and screw-mounted anvil blade made of high-quality hardened steel / clean, precise cut / all parts can be replaced
- Efficient: easy, durable cutting adjustment / wire cutting notch / sap groove
- Ergonomic: hand and wrist protection and optimisation of the force exerted are provided by the ideal shape of the handles, the angled head and the cushion-shock absorber / non-slip coating



# Our recommendation (1 \*: Recommended, 2 \*: Strongly recommended, 3 \*: Best fit)

Viticulture	***
Arboriculture	***
Horticulture	***
Parks and Gardens	***
Nursery	***
Small hand	***
Large hand	***
Left-handed	***



#### The points of excellence



## Forged aluminium handles guaranteed for life\*

Lightweight, strong and sturdy thanks to special aluminium alloys and advanced precision forging methods perfectly mastered by FELCO.



### Ergonomic tool

Inclined cutting head to reduce the risk of muscular-skeletal injuries and to maximise user comfort.



### Shock absorption system

FELCO's special cushion stops reduce impact at the end of a cut, protecting hand and wrist.



## Precision adjustment system

FELCO's micrometric adjustment system guarantees an optimal adjustment of the cutting head throughout the life of the tool, and delivers a clean and precise cut every time.



#### Sap groove

The sap groove prevents the blade sticking when cutting "sappy" wood. It saves time and makes pruning easier by removing sap and debris after each cut.



#### Wire cutting notch

The blades of most FELCO pruning shears feature a notch that allows for the cutting of small wires without damaging the cutting edge.

#### Accessories



FELCO 300

Picking and Trimming Snip

For a clean cut



FELCO 310

Picking and Trimming Snip

For grape harvesting





Sharpening tool

Sharpening stone



FELCO 903

Sharpening tool

Sharpener











FELCO 910

Holster

Leather - With belt loop and clip

FELCO 912

Holster

Leather - With belt clip

FELCO 913

Holster
In mock leather - With belt loop

FELCO 980

Maintenance product

Spray




FELCO 990

Maintenance product

Grease



# Spare parts



	REF.	Designation	Composition	UCC bar code
000	2/30	Adjustment key	1x 2/30	
	7/3	Blade	1x 7/3	7 83929 40004 4
<b>S</b>	7/4	Anvil-blade with screw	1x 7/4 + 1x 7/6	7 83929 40012 9
E ○ ==	7/90	Kit	1x 7/7 + 1x 2/16 + 1x 2/9 + 1x 7/8	7 83929 40017 4
	2/91	Kit	2x 2/11	7 83929 40018 1
A: 8:	2/92	Kit	1x 2/15 + 1x 2/18 + 1x 2/14 + 1x 2/12 + 1x 2/13 + 1x 2/20	7 83929 40020 4
11 111	2/93	Kit	4x 2/18 + 6x 2/20	7 83929 40021 1
<b>○</b> ==>	7/94	Kit	1x 2/9 + 1x7/8	7 83929 40028 0
OF THE RESERVE OF THE PERSON O	8/1	Handle without blade	1x 8/1 + 3x 7/5B + 1x 2/19 + 1x 2/20 + 1x 7/10 + 1x 2/13 + 1x 2/12 + 1x 2/14 + 1x 6/35	



E.	7/2	Handle without anvil- blade	1x 7/2 + 1x 2/18 + 1x 7/36
~	6/35	Plastic coating for blade handle	1x 6/35
<u> </u>	7/36	Plastic coating for anvil- blade / anvil handle	1x 7/36
0	7/5B	Rivet for blade	1x 7/5B
<b></b> }	7/6	Screw for anvil-blade	1x 7/6
==)	7/8	Bolt	1x 7/8
0	2/9	Nut	1x 2/9
=	7/10	Bush	1x 7/10
annonna.	2/11	White spring	1x 2/11
<b>&amp;</b>	2/12	Thumb catch	1x 2/12
0	2/13	Spring for thumb catch	1x 2/13
<b>\$</b> 100	2/14	Screw for thumb catch	1x 2/14
	2/15	Catch plate	1x 2/15
<b>¥</b> 0	2/16	Locking segment	1x 2/16
	7/7	Screw for locking segment	1x 7/7
Þ	2/18	Cushion	1x 2/18
0	2/19	Edging	1x 2/19



•

2/20

Shock absorber

1x 2/20

#### Maintenance









#### Cleaning

It is advisable to clean your tool after each use.

If your tool is particularly dirty or subject to rusting after exposure to moisture, do not delay cleaning.

#### Oiling

After cleaning, it is advisable to oil the tool so as to protect it from corrosion. The oil will also unjam the tool.

#### Sharpening

It is advisable to sharpen your tool at least once a day, but if you feel that your tool is not cutting as well as usual, sharpen it right away!

#### Dismantling

It is advisable to dismantle your tool on a regular basis, but at the very latest when it appears to be jammed.



### Replacement parts













#### Changing the blade

When the blade and the anvil-blade no longer cross, or when the blade is badly damaged, it is advisable to change it.

Regulate the working of the blade and anvil-blade by adjusting the tightening of the nut. The blade should rub against the anvil-blade over 2/3 of its length.

### Changing the anvil-blade

When the blade and anvil-blade no longer cross and the anvil-blade is badly damaged, it is advisable to change it.

#### Changing the shock absorber

When the tool closes too abruptly during pruning, and the cushion is in good condition, the shock absorber should be changed.

### Changing the cushion

When the tool closes too abruptly during pruning and the shock absorber is in good condition, the cushion must be changed.

#### Changing the thumb catch

When the thumb catch is damaged and loosens when used, even when the screw is readjusted, change it.

#### Changing the plastic coatings for handles

If the coatings are badly damaged, you can replace them.

Soak the coatings for 2 minutes in boiling water - recommended glue: Loctite 415.